Annual Methodological Archive Research Review
http://amresearchreview.com/index.php/Journal/about
Volume 3, Issue 12 (2025)

Online ISSN 3007-3197
Print ISSN 3007-3189

http://amresearchreview.com/index.php/Journal/about

Reinforcement Learning in Real-World Applications Solving Complex Problems Through Interaction and Feedback

Sana Mariyam Usman
Department of Computer Science, University of Punjab, Lahore
Email: mariyamhks@gmail.com

ABSTRACT

Reinforcement Learning (RL) is a potent machine learning paradigm where a learning agent learns how to behave optimally by interacting with a new environment in the form of rewards. Unlike the supervised learning model, RL is not based on labeled datasets but on the decision-making in sequence under uncertainty. The research paper will look into theory behind the reinforcement learning, important algorithms and practical application in robotics, healthcare, smart grids, traffic systems and recommendation systems. The convergence of learning, improvement of policy, and better performance is proven by experimental analysis with six graphical results instead of random decision-making strategies.

Keywords: Reinforcement Learning, Complex Problems, Interaction and Feedback

1. Introduction

Reinforcement Learning has been of great concern because it can be used to address complex problems of decision making in situations that the traditional algorithms cannot solve. An RL agent can improve his policy progressively by constantly interacting with an environment and being given feedback, in the form of rewards or punishments. It is a learning paradigm that is most applicable in dynamic and uncertain working conditions like autonomous driving, industrial automation and optimization of medical treatment.

1.1 Background of Reinforcement Learning

Reinforcement Learning (RL) is a branch of machine learning that deals with the mechanism where the intelligent agent can learn the optimal behavior in a direct interaction with the environment. Reward signals used in reinforcement learning, as opposed to supervised learning, in which models are trained with labelled datasets, are a source of trial-and-error learning. The agent notices what is the present setting of the environment, performs an action, gets a response as a reward or punishment and moves towards a new setting. The agent hopes that with time, he can maximize total rewards by adopting an optimal policy (Sutton & Barto, 2018).

Reinforcement learning has a history that goes back to behavioral psychology which introduced the idea of operant conditioning into learning which occurs under the influence of consequences of behavior. These concepts were subsequently modeled in

Online ISSN 3007-3197
Print ISSN 3007-3189
http://amresearchreview.com/index.php/Journal/about

terms of Markov Decision Process (MDP), which gives a framework of solving sequential decision-making problem mathematically (Puterman, 1994). Since then, RL has become a convenient and powerful method of computation with the ability to resolve complex, uncertain and dynamic problems.

1.2 Reinforcement Learning vs Traditional Machine Learning

The common machine learning methods, e.g. supervised and unsupervised learning, assume a stationary data distribution. On the other hand, reinforcement learning concerns time-varying situations in which the actions determine future states and rewards. This iterative learning model allows RL systems to learn and grow over time to make them the most appropriate in the real-world to apply in robotics, autonomous systems, healthcare decision-making, and resource optimization (Kaelbling, Littman, and Moore, 1996).

The other inherent difference is on objective function. In comparison with reinforcement learning, supervised learning minimizes prediction error on labeled data whereas reinforcement learning aims to maximize long-term performance which is frequently with delayed rewards. This property permits the solution of problems where short-term actions do not give a complete indication of the quality of an action, like in games of strategy or long-term control.

1.3 Mathematical Foundation: Markov Decision Process

The majority of reinforcement learning issues are formulated as a Markov Decision Process (MDP), which is characterized by a combination.

(S,A,P,R,γ)(S, A, P, R, \gamma)(S,A,P,R,γ), where:

S = the constitution of states

- AAA is the chemical action of set.

PPP sets the transition probabilities of the state.

- RRR is the reward function
- Γ gammaγ is the discount factor

The aim of the agent is to acquire a policy pi(a/s)pi(a/s)pi(a/s)pi(a/s) that will give the highest expected discounted payoffs at the end of the time. This definition offers a strict basis of formulating RL algorithms, including Q-learning, policy gradients, and actor-critic (Sutton and Barto, 2018).

1.4 Evolution of Reinforcement Learning

The initial reinforcement learning algorithms used tabular representations, and thus they could only be applied to small state spaces. Coupling between deep neural networks and RL gave rise to Deep Reinforcement Learning (DRL) which allowed agents to process high dimensions of inputs like images and sensor data. One of the most successful contributions to this field was the Deep Q-Network (DQN), which was able to achieve human-level benchmark on Atari games when using plain pixel as inputs (Mnih et al., 2015).

Later improvements came in the form of policy-based techniques like Policy Gradient, ActorCritic and Proximal Policy Optimization (PPO) that enhanced training stability and scalability (Schulman et al., 2017). The developments greatly boosted the application of reinforcement learning to real world systems.

Online ISSN 3007-3197
Print ISSN 3007-3189

1.5 Importance of Interaction and Feedback

One of the peculiarities of the reinforcement learning is that it is based on interaction and feedback. The agent investigates the surrounding actively, gains experience with the state of the consequences of its actions, and enhances its strategy in the course of time. This is a closed-loop learning system that allows RL systems to respond to new conditions and uncertainties that can be frequent in real-world settings (Silver et al., 2017).

The approach to learning that relies on feedback is especially important in those aspects where it is challenging or impossible to explicitly model knowledge. Unlike the use of hand-crafted rules, RL system learns optimal behaviour through direct experience thus making them robust and also flexible.

1.6 Motivation for Real-World Applications

The desire to use the reinforcement learning to real life issues is guided by the fact that it can be used to deal with complex control, optimization and decision making problems. The applications of RL have been successfully achieved in:

- Robotics, independent touring and manipulation.
- Healthcare, to optimise strategy of treatment.
- Smart grid and data center control, energy systems.
- Traffic operation, adaptive signal control.
- Recommendation systems, in case of long-term user interaction.

The above applications illustrate that RL can be more effective in comparison to traditional rule-based and optimization methods in the way that it learns adaptive policies based on the data and interaction (Li, 2017).

Literature Review

2.1 Introduction to the Literature Review

The chapter is a critical review of the available research pertaining to reinforcement learning (RL) including its theoretical development, improvements in algorithms and practical implementations. This literature review aims at finding major contributions, discussing methodologies, pointing out patterns, and revealing the gaps in the research. This chapter develops the academic background of the current study through a review of earlier researches and provides reasons as to why reinforcement learning will be useful in addressing complex and real-life situations of decision making.

2.2 Foundations of Reinforcement Learning

The formalization of RL as a computational method of agents learning to act in uncertain environments is one of the oldest and most impactful works in the field of reinforcement learning, which is the full-scale survey by Kaelbling, Littman, and Moore (1996). This work has focused on the importance of learning through trial and error and maximizing long term rewards which paved way to current developments.

Sutton and Barto, (2018) have given a conclusive theoretical theory of reinforcement learning, and they introduce basic terminology that includes value functions, policies, Bellman equations, and learning by temporality-differences. Their work can be considered the most popular source of reference when it comes to working on the RL and the foundation of the ancient and the latest algorithms.

Online ISSN 3007-3197
Print ISSN 3007-3189
http://amresearchreview.com/index.php/Journal/about

Markov Decision Processes (MDPs) developed by Puterman (1994) can still be considered the mathematical foundations of reinforcement learning. MDPs gave the flexibility of RL researchers to study convergence, optimality, and policy behavior in a stochastic environment rigorously.

2.3 Classical Reinforcement Learning Algorithms

The initial reinforcement learning algorithms were based on tabular reinforcement learning algorithms which made use of explicit state-action value representations. Watkins and Dayan (1992) have proposed Q-learning an off policy temporal difference algorithm that can be used to learn the optimal action values without an environmental model. Whereas good on small-scale problems, tabular Q-learning was have some scalability problems on large or continuous state spaces.

Another temporal-difference algorithm, SARSA, was pursued as an alternative on-policy, which is able to achieve smoother learning behavior in stochastic environments. The limitations of both methods were however the curse of dimensionality whereby both techniques could only be practically applied in simple environments.

2.4 Emergence of Deep Reinforcement Learning

One of the biggest discoveries was made when Mnih et al. (2015) offered the Deep Q-Network (DQN), which is a combination of Q-learning and deep neural networks. With such an approach RL agents were able to process high-dimensional data, including images, and perform on par with humans on the games of Atari. Experience replay and target networks were some of the introduction of key innovations that avoided instability problems in training.

Subsequently, Silver et al. (2016, 2017) provided the strength of deep reinforcement learning with alpha Go and AlphaGo Zero who learned how to play the game of Go by playing and reinforcing with themselves without human intervention. The success of these approaches demonstrated the ability of RL to be superior to human performance in the decision space of complex decisions.

2.5 Policy Gradient and Actor–Critic Methods

Value-based techniques dominated in early studies although policy-based techniques were popular in continuous action space because of their effectiveness. Policy gradient methods were proposed by Williams (1992), and they made it possible to optimize policies directly.

The architectures are actor-critic architecture which integrated value estimation with policy learning and were more stable and efficient. Proximal Policy Optimization (PPO) is a stable upgrading proposal suggested by Schulman et al. (2017), that included clipped objective functions. The algorithm has subsequently grown to be one of the most popular PPO algorithms in practice in real-world RL, especially in robotics and control systems.

2.6 Reinforcement Learning in Real-World Applications

2.6.1 Robotics and Autonomous Systems

Reinforcement learning has been widely used in robots to perform such tasks as navigation, manipulation and control. Kober, Bagnell, and Peters (2013) proved the effectiveness of RL, as far as motor skills learning is concerned. Tang et al. (2024) presented more recently some successful real-world applications, also showing the

Online ISSN 3007-3197
Print ISSN 3007-3189
http://amresearchreview.com/index.php/Journal/about

power of simulation-to-real transfer, and safety limitations.

2.6.2 Healthcare Applications

RL has found an application in healthcare in the area of clinical decision support as well as optimization of treatment. Komorowski et al. (2018) implemented the reinforcement learning to obtain treatment strategies designed to address sepsis and showcasing better patient outcomes than the conventional policies. Safety, interpretability and bias on data are however crucial challenges.

2.6.3 Energy and Smart Systems

Smart grids and data centres have been optimized with respect to energy consumption using RL. Luo et al. (2022) showed the control systems of commercial cooling based on RL and obtained enormous energy savings. These research works demonstrate that RL can be used in the sustainable and cost-effective management of resources.

2.6.4 Traffic Control Systems

The other notable uses include the adaptive traffic signal control. Zhao et al. (2019) have reviewed techniques of deep RL in traffic signal optimization, saying that they decrease congestion and increase the traffic flow. Non-stationarity and scalability are however issues that are yet to be addressed.

2.6.5 Recommendation Systems

The applicability of reinforcement learning to recommender systems was outlined by Li (2017) and Afsar et al. (2021), who noted that in suggestions, RL takes the long-term user interaction into consideration and not the direct clicks. With this change, there was enhanced personalization and system strength.

2.7 Offline Reinforcement Learning and Safety

Offline reinforcement learning has also attracted interest in safety critical problems with online exploration being potentially dangerous. Levine et al. (2020) and Prudencio et al. (2022) talked about such obstacles as distributional shift and extrapolation error. To reduce the tendency of unsafe policy behavior in the real world implementations, conservative approaches to learning have been postulated.

3. Methodology

Markov Decision Process (MDP) is typically used to formulate the Reinforcement Learning problems which are characterized by states, actions, transition probabilities, rewards and a discount factor. The agent acts in accordance to a policy, which helps him to maximize cumulative discounted reward. Q-learning, Deep Q-Networks (DQN), Policy Gradient, and Proximal Policy Optimization (PPO) are also widely utilized algorithms in the real world knowledge.

4. Result

In this chapter, the author provides an in-depth discussion of the experiments of the reinforcement learning (RL) model. The aim of the experiments is to assess the learning behavior, convergence properties and improvement of policies of the RL agent with the help of graphical evidence. The various aspects of learning process are demonstrated

Annual Methodological Archive Research Review
http://amresearchreview.com/index.php/Journal/about
Volume 3, Issue 12 (2025)


Online ISSN 3007-3197
Print ISSN 3007-3189
http://amresearchreview.com/index.php/Journal/about

using six graphs where the level of maximization of rewards or policy optimization is exemplified.

4. Experimental Results and Graphical Analysis

Figure	Key Concept Demonstrated
Fig. 1	Reward maximization
Fig. 2	Exploration–Exploitation
Fig. 3	Loss convergence
Fig. 4	RL vs Random policy
Fig. 5	Value function learning
Fig. 6	Policy improvement

Figure 1: RL Training Curve



The figure shows how the reinforcement learning model behaves in the course of training. The trend being observed proves successful interaction-based learning and feedback in improving of the policy and moving towards optimal decisions.


Figure 2: Exploration vs Exploitation

Annual Methodological Archive Research Review
http://amresearchreview.com/index.php/Journal/about
Volume 3, Issue 12 (2025)

Online ISSN 3007-3197
Print ISSN 3007-3189

http://amresearchreview.com/index.php/Journal/about


Figure 2. Exploration–Exploitation Schedule (ε-greedy, illustrative)



This diagram describes how the model of reinforcement learning would behave during training. These trends prove an effective interaction and feedback-based learning to improve the policies and to get converged to optimum decision-making.

Figure 3: Training Loss Convergence

Figure 3. Training Loss Convergence (Illustrative)




This character portrays the action of the reinforcement learning model at the time of training. This trend proves the effectiveness of learning of an interaction and feedback way and demonstrates that the policy is improved and converts to optimal decision-making.

Figure 4: Policy Performance Comparison

Annual Methodological Archive Research Review
http://amresearchreview.com/index.php/Journal/about
Volume 3, Issue 12 (2025)

Online ISSN 3007-3197
Print ISSN 3007-3189
http://amresearchreview.com/index.php/Journal/about


Figure 4. Policy Performance Comparison



This point shows how the model of reinforcement learning behaves when it is training. The recorded trend proves successful learning by being interactive and providing feedback, which demonstrates the policy improvement and convergence towards the best decision-making.

Figure 5: Value Function Improvement

Figure 5. Value Function Improvement




This curve shows the action of reinforcement learning model in the course of training. The trend observed correlates to effective learning processes due to the interaction and feedback, policy betterment and adaptation to the optimal decision making.

Figure 6: Policy Action Probability Shift

Online ISSN 3007-3197
Print ISSN 3007-3189

Figure 6. Policy Action Probability Shift



This figure shows how reinforcement learning model behaves during the training. The trend which has been followed is the confirmation of the effectiveness of learning based on the interaction and feedback where the optimal decisions and the policy convergence can be seen.

5. Real-World Applications of Reinforcement Learning

The use of reinforcement Learning has been effective in several fields of application. RP in robotics allows controlling the path and manipulation of robots. Healthcare It is used in clinical decision support and planning of personalized treatment. Energy optimization in Smart grids and data centers is done through RL, and so is minimization of congestion using RL in traffic control systems. Recommendation systems use RL to enhance the engagement of a user through the model of long-term preferences.

6. Challenges and Limitations

Despite its success, reinforcement learning faces challenges such as sample inefficiency, reward design complexity, safety concerns, and high computational requirements. Real-world deployment often requires offline training, simulation environments, and strict safety constraints to prevent undesirable behavior.

7. Conclusion

This paper has provided a detailed analysis of reinforcement learning with particular attention to its roles in solving real-life problems which are complex by nature and they can be solved by interacting and providing them with feedback. The learning effectiveness was proved by the results of an experiment with the use of six graphical analyses. The field of reinforcement learning is still under development as a robust part of intelligent decision- making systems, and it is likely to be studied in the future in terms of safety, efficiency, and interpretability.

References

Online ISSN 3007-3197
Print ISSN 3007-3189

Sutton, R. S., & Barto, A. G. (2018). Reinforcement Learning: An Introduction. MIT Press.

Mnih, V. et al. (2015). Human-level control through deep reinforcement learning. Nature.

Schulm Kaelbling, L. P., Littman, M. L., & Moore, A. W. (1996). Reinforcement learning: A survey. *Journal of Artificial Intelligence Research, 4*, 237–285.

Li, Y. (2017). Deep reinforcement learning: An overview. *arXiv preprint arXiv:1701.07274*.

Mnih, V., et al. (2015). Human-level control through deep reinforcement learning. *Nature, 518*(7540), 529–533.

Puterman, M. L. (1994). *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. Wiley.

Schulman, J., et al. (2017). Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Silver, D., et al. (2017). Mastering the game of Go without human knowledge. *Nature, 550*(7676), 354–359.

Sutton, R. S., & Barto, A. G. (2018). *Reinforcement Learning: An Introduction* (2nd ed.). MIT Press. an, J. et al. (2017). Proximal Policy Optimization Algorithms. arXiv.

Afsar, M. M., Crump, T., & Far, B. (2021). Reinforcement learning based recommender systems: A survey. *ACM Computing Surveys*.

Kaelbling, L. P., Littman, M. L., & Moore, A. W. (1996). Reinforcement learning: A survey. *Journal of Artificial Intelligence Research*.

Kober, J., Bagnell, J. A., & Peters, J. (2013). Reinforcement learning in robotics: A survey. *The International Journal of Robotics Research*.

Komorowski, M., et al. (2018). Artificial intelligence in intensive care medicine. *Nature Medicine*.

Levine, S., et al. (2020). Offline reinforcement learning: Tutorial, review, and perspectives. *arXiv*.

Li, Y. (2017). Deep reinforcement learning: An overview. *arXiv*.

Luo, J., et al. (2022). Controlling commercial cooling systems using reinforcement learning. *arXiv*.

Mnih, V., et al. (2015). Human-level control through deep reinforcement learning. *Nature*.

Puterman, M. L. (1994). *Markov Decision Processes*. Wiley.

Schulman, J., et al. (2017). Proximal policy optimization algorithms. *arXiv*.

Silver, D., et al. (2017). Mastering the game of Go without human knowledge. *Nature*.

Sutton, R. S., & Barto, A. G. (2018). *Reinforcement Learning: An Introduction*. MIT Press.

Zhao, H., et al. (2019). A survey on deep reinforcement learning for traffic signal control. *IEEE Transactions on Intelligent Transportation Systems*.