

Intelligence based Self-Healing Network Design: An Automated Incident Response System for Troubleshooting of IoT Security Breaches

Muhammad Hamza Akhtar* (Corresponding Author)

Department of Information Technology, Faculty of Computer Science & Information Technology, Superior, University Lahore, 54000, Pakistan
muhammadhamza.docs@gmail.com

Tayyba Jabeen

Department of Software Engineering, Faculty of Computer Science & Information Technology Superior, University Lahore, 54000, Pakistan
tayyabajabeen60@gmail.com

Rimsha Aziz

Department of Information Technology, Faculty of Computer Science & Information Technology Superior, University Lahore, 54000, Pakistan
SU92-MSITW-F24-007@superior.edu.pk

Muhammad Nabeel Amin

Department of Computer Science, Government College University, Faisalabad
nabeelofficial70@gmail.com

Syed Muhammad Rizwan

Department of Computer Engineering, University of Engineering and Technology Lahore, Pakistan
rizwan.naqvi@ieee.org

Khalid Hamid

Department of Computer Science & Information Technology, Superior University Lahore, 54000, Pakistan
Khalid6140@gmail.com

ABSTRACT

Integration of the Internet of Things (IoT) into various application domains not only expands capabilities but also brings forth a multitude of challenges. With the advancement of communication and computer technology, network architectures have become increasingly complex, accompanied by the continual emergence of novel services. This increase in sophistication surpasses the abilities of manual maintenance and traditional network management solutions. Ever increasing in adoption of Internet of Things (IoT) devices has largely increased the coverage of attack surfaces to cyber threats which has put manual

incident response process at a disadvantage. AI-ML based automated incident response systems (AIRS) promises an ambitious change using AI/ML orchestration to autonomously identify, contain and mitigate the security attacks in IoT. We explore AIRS for IoT in this paper looking specifically at self-healing network architectures displacing breached devices and containing attacks automatically (i.e., without any human in the loop). According to new research incorporating AI into self-healing network systems allows such systems to respond to an incident and substitute compromised devices autonomously. This article proposed a mechanism Automated incident Response Systems (AIRS) based on AI-ML. The proposed system reduces response time, effect of security breaches and assists organizations to sustain the continuity of operations. These systems rely on AI-driven behavioral monitoring to ensure there are constant checks on network traffic, devices in use and anomalies that could pose security incidents. The ability to conduct real-time analysis provides an opportunity to be proactive against the possible threats. Self-healing architectures isolate and replace compromised devices automatically making the network usable as well as secure. Such proactive step also minimizes downtime and general system robustness. Automation of incident response activity reduces the reliance on human operators by AIRS. The teams of cybersecurity professionals can work on strategic decisions and difficult incidences as opposed to routine actions. As IoT environments increase, scalability and ability to dynamically adjust to higher network devices and threats are major features in AIRS. New data allow AI models to improve their effectiveness as they learn. The use of AIRS in such domains as smart cities and industrial IoT where immediate response to security threats should be provided is reflected in the successful deployment of the technology in case studies. These studies have indicated that AIRS helped organizations achieve great improvements of mean time to respond (MTTR) to incidents with some reporting tremendous improvement of up to 70% using AIRS as compared to traditional forms. Potential advances could involve applying federated learning to the privacy and security of AIRS so that organizations can work together on threat intelligence without having to exchange sensitive data. Further improvements in AI and ML will even better the capacities of AIRS which will equip them to keep up with the emerging cyber threats as well as enhance their defensive approaches.

Keywords

Automated Incident Response System, Machine Learning, Artificial Intelligence, Self-Healing Networks, Internet of Things, Cybersecurity, Threat Detection

1. Introduction

IoT devices are everywhere from health care to manufacturing and from smart homes to critical infrastructure. Their interconnectedness and diversity give rise to new security concerns such as constrained device capabilities, no universal mechanism for updating devices and no standard network security protocols [1]. Response to alerts cannot scale with the large amount of alerts that need to be handled together with the velocity bearers now travel. AIRS are designed to overcome these limitations by automating the retrieval, analysis, response to security alerts, allowing real-time, scalable and uniform responses to security incidents [2, 3]. This paper seeks to explore the design and operation of self-healing networks

in AIRS with a focus on the capability of the network to autonomously quarantine IoT devices that have been compromised to contain the threat. The security challenges of IoT are due to the resource-constrained nature (limited processing power, memory, and energy) [4, 5] update insecure mechanisms and manual response tasks. These are addressed by Automated Incident Response Systems (AIRS) through: Figure 1 shows the working architecture to monitor device and network activities in real time and embedded agents are monitoring network and system traffic [6, 7]. Anomaly threat detection (e.g., identify suspicious command patterns) [8]. Detects compromised devices, virtualizes, shuts down and enables the smooth resumption of operations using automated workflows [9]. Lightweight encryption and authentication decrease computational overhead on IoT devices [10]. AI correlates alerts (e.g., anomalous traffic from industrial robots). Isolates device and forces micro-segmentation (to prevent lateral movement). Changes networks and activates backups [11].

It include user profiles, prevents unauthorized updates and protects your data from vulnerabilities. It firmware integrity with digital signatures to prevent attacks. Updating stacks via update channels that are kept encrypted and secure. AIRS decrease response times from hours to seconds, reduce false positive by 40-60% and offer 7-day-a-week monitoring [12, 13]. If a compromised smart thermostat is detected it is quarantined within a few seconds deterring smart home network intrusions.




Figure 1: Self-Healing Networks Architecture [6]

$$R^2 = 1 - \frac{\sum_{i=1}^n (Y_i - \hat{Y}_i)^2}{\sum_{i=1}^n (Y_i - \bar{Y})^2} \quad \text{Eq (1)}$$

Explosion of IOT devices has opened huge attack surfaces for cyber threats that can inundate manual incident response operations. With the evolving nature of the IoT threat landscape it becomes difficult to quickly detect, isolate and even mitigate attacks on IoT networks, systems and devices in a timely manner due to specific security challenges which IoT environments present including but not limited to limited device resources varying update mechanisms as well as lack of standardized protocols [14, 15]. Manual responses are not fast enough and lack the repeatability to react at the scale and speed that new attacks have making it alarmingly timely for an automated, scalable and repeatable system to independently secure IoT on the fly.

$$RMSE = \sqrt{\frac{1}{n} \sum_{i=1}^n (Y_i - \hat{Y}_i)^2} \quad \text{Eq (2)}$$




Figure 2: A holistic Design for maintenance based on self-healing Architecture [16]

1.1 Self-Healing for Cyber-Physical Systems

A self-healing system is equipped with measures to identify and prevent attacks from internal or external events and to facilitate the system's recovery autonomously. The analysis of IoT expansion has made me realize some unpleasant security concerns. AIRS is an automated IoT security framework that constitutes one of the most powerful tools that I have met in dealing with these problems [17, 18]. In order to understand why AIRS can be important consider a huge system of smart home thermostats, surveillance cameras and other electronic gadgets. They all can be hacked and a single breach can drag down the entire network. Traditional response methodologies of identifying an issue, investigating and correcting it fail on thousands of endpoints [19, 20]. AIRS addresses that issue by ensuring swifter time to respond and lower false positive levels, which will allow the system to identify the threats 24/7. There are some metrics to address why that works below mentioned table 1 shows the

Comparative Analysis of Methods used for IOT Security.

Table 1: Comparative Analysis of Methods used for IOT Security

Ref	Aspect	Dataset	Network Architecture	Algorithm/Model Used
[21, 22]	Response Time Reduction	Decreased from hours to seconds for incident response	Fast Decision Network	Twin Model
[23, 24]	False Positive Rate Reduction	Reduction of 40-60% in false positives	Multi-Area Microgrid	QoS Model
[25, 26]	Monitoring Availability	24/7 continuous monitoring of IoT devices and networks	Strategy Network	Auto-Regressive Moving Average with Exogenous Input Model
[27, 28]	Compromised Device Quarantine Time	Quarantine of compromised devices (e.g., smart thermostat) within seconds	Intrusion Detection System	Convolutional Neural Network
[29, 30]	Resource Constraints	Limited processing power, memory, and energy in IoT devices	Agent Architecture	Artificial Neural Network
[31, 32]	Update Mechanisms	Insecure and varied update mechanisms for IoT devices	Host Intrusion Detection System	Supervised Knowledge Base Algorithm
[33, 34]	Standardization Issues	Lack of universal network security protocols		Genetic Algorithm
[35, 36]	Self-Healing Capabilities	Autonomous quarantine and recovery of compromised devices	Fast Decision Network	Naive Bayes
[37]	Anomaly Detection	Identification of suspicious command patterns and anomalous traffic	Multi-Area Microgrid	DBSCAN Algorithm
[38, 39]	Micro-segmentation	Isolation of devices to prevent lateral movement of threats	Strategy Network	Long Short-Term Memory (LSTM)
[40, 41]	Firmware Integrity	Use of digital signatures to ensure firmware integrity and prevent attacks	Valuation Network	Auto-Regressive Moving Average (ARMA)
[42, 43]	Encrypted Update Channels	Secure and encrypted channels for firmware	Fast Decision Network	Monte Carlo Tree Search

		updates		
--	--	---------	--	--

Above table summarizes critical metrics and findings related to the implementation of AIRS in IoT environments. Comparing these metrics one can see that AIRS has the potential to enhance IoT security in spite of the large number of devices, the peculiarities of resource constraints and the weaknesses of update mechanisms and standardization [44].

$$TDI = \sqrt{(\Delta C)^2 + (\Delta \sigma)^2} \quad \text{Eq (3)}$$

Automation is essential to maintaining the process of IoT growth in the current rate then since it is one of the ways to increase the security as well as provide an adaptable and scalable solution to the complex world of networked IoT devices [45].

$$MCC = \frac{TP * TN - FP * FN}{\sqrt{((TP + FP) * (TP + FN) * (TN + FP) * (TN + FN))}} \quad \text{Eq (4)}$$

ELU – E- Linear Unit with $0 < \alpha$ is

$$f(x) = \begin{cases} \alpha(\exp(x) - 1) & \text{for } x < 0 \\ x & \text{for } x \geq 0 \end{cases} \quad \text{Eq (5)}$$

$$\delta_h = 60^\circ \begin{cases} 0 + \frac{(\beta_g - \beta_b)}{(m_x - m_n)}, \text{ if } m_x = \beta_r \\ 2 + \frac{(\beta_b - \beta_r)}{(m_x - m_n)}, \text{ if } m_x = \beta_g \\ 4 + \frac{(\beta_r - \beta_g)}{(m_x - m_n)}, \text{ if } m_x = \beta_b \end{cases} \quad \text{Eq (6)}$$

1.2 Real-Time Threat Forensics and Detection based on AI & ML

The real advantage of a CAE is that it uses AI and ML to analyze massive data. AI and ML methods can help create normal baselines of system/device operation. After such baselines are defined the engine can then flag deviations (i.e. anomalies) as potential threats. So, if an IoT device begins flooding an unknown external IP with gigabytes of data for example this could be labeled as suspicious behavior. ML algorithms trained to detect patterns of know attack methodologies. For example, the engine may identify typical patterns of malware communication or particular network behavior that can be indicative of a botnet or a DDOS attack [46, 47]. The engine can predict possible future risks and vulnerabilities based on the

historical data it has computed. This permits proactive steps including patching or security configurations being tightened before an attack takes place [48, 49].

The engine may take in threat intelligence feeds from external sources (e.g. known threat databases) and correlate incoming data with this external intelligence to recognize known attack signatures or tactics. CAE can discover security threats in real time upon threat detection of the unusual patterns or unusual ties. Some of the threats it can detect are attempting to gain unauthorized access to devices or networks. Participating in massive DDoS attacks from IoT devices.

From the above Equations (4) (5) and (6), m_x represents the maximum pixel while m_n Shows the minimum pixel. The color features are extracted at the hidden layer as shown below in Eq 7.

$$\delta_s = \left(\frac{m_x - m_n}{m_n} \right) \quad \text{Eq (7)}$$

$$\delta_v = m_x(\beta_r, \beta_g \beta_b,), \delta_{sv} = m_n(\beta_r, \beta_g \beta_b,) \quad \text{Eq (8)}$$

Outbound transfer of data from the network to an external location. Malicious or unintentional activities conducted by users or devices with authorized access. By recognizing these threats on-the-fly the system is able to jump to the next phase responding to the threat [50, 51].




Figure 3: A holistic Design for network forensics and AI in self-healing Architecture [52]

1.3 Automated Response Workflows

The central analyzer can activate response workflows after it identifies a threat. These are predetermined actions the system can initiate to respond to the threat. There are also automatic responses for example upon discovering a compromised device the engine can automatically quarantine it from the rest of the network to stop the malware from spreading or the data from being stolen [53]. The system may alert human security analysts of a detected threat providing sufficient detail to assist in investigation and further action. If a (DDoS) attack is detected the system could drop or reroute the bad traffic to another location to handle the attack. In the event of a major attack the engine would be able to launch a full-scale incident response, process that kicks off containment, incident response and recovery [54]. After a response workflow is initiated the central engine assist to investigation of the incident by providing comprehensive logs and data of the event.

$$R(t) = \sum_{i=1}^n FI_i(t) * \tau_{ih} + [\tau_h * r_{i-1}] \quad \text{Eq (9)}$$

What were the actions paving the way for the incident? What was affected on the network? What did they do to me? What files, processes or external IPs were exercised? This is critical information that security teams need in order to have full an understanding of the scope of the attack, to better protect and remediate and be certain that the attack is truly thwarted. The conventional security implementations are rule or signature-based and they may not detect new or evolving threats. AI and ML can be used to allow the system to learn and adapt according to new data thereby enhancing its ability to detect new attacks [55, 56]. For example, the technology could pick up on what “normal traffic” is for say a particular IoT device and then flag any variance as being potentially malicious despite not having seen that type of attack before. AI models work images and footage to avoid "false positives" that make traditional security systems a headache. If trained properly the system can learn that what might otherwise appear to be a bad thing happening is actually just a benign event (like a legitimate firmware update). This reduces time spent performing further investigations on non-issues even if a human still needs to verify the positive indication [57].

1.4 Network Forensics

NF plays a crucial role in assisting investigators in extracting valuable evidence from network traffic. Investigators aim to uncover specific information within the network traffic that serves as evidence in their investigations. As the volume of the IoT network increases or more devices are added the AI and ML capabilities of the centralized engine can also scale [58, 59]. They are able to process and analyze data from thousands or millions of devices in real time so new devices won't mean new blind spots in detecting threats. With data analysis and response workflows automated by the system threats can be reacted to in a fraction of the time versus the manual approach, reducing the impact and halting the spread of attacks. By being able to anticipate potential threats and recognize anomalies in advance the engine prevents threats and makes it less likely that an attack is successful [60].

The ability of real-time monitoring and automation with AI-driven analysis helps enhance an organization's security status especially in an IoT-intensive environment where manual monitoring is not feasible. With the automation of many elements of threat detection and

response organizations can reduce the biggest set of security costs, labor and cost associated with security operations [61, 62].

2. Literature Review

Automated response exists where software, AI and ML are used to monitor, detect and response to security incidents without any human involvement [63]. Key benefits include: Automated containment and incident response responses lose response time and fast response in low coverage window [64]. Automation enables users and tools to take action to respond quicker to a security threat. Rather than relying on a human to look into it and take appropriate action. Automated systems can quarantine an infected device or block malicious traffic, remove malware & reset the compromised credentials. It means automation accelerates responses to cyber threats and minimizes potential damage [65].

For example a business gets phishing email that deceives an employee into clicking on a malicious link. If you did these steps would look like this without automation it take hours or even days before the employee reports the email to IT. Security team research the email and the link. They will manually quarantine the infected device. They look for other members who were mailed the same message. They block malicious traffic link and delete the email from inboxes. That process can take hours or even days during which the danger could spread or steal information [66, 67].

$$Y(t) = \omega[\tau_{ho} * h(t)] \quad \text{Eq (10)}$$

With automation the security system automatically identifies the legitimate email using threat intelligence. It isolates the email before the intended recipient sees it. When the link is clicked the system will automatically quarantine the device from the network. Then it deletes matching emails from all inboxes. Security team gets warning but important steps already being taken. However the whole process occurs in seconds or a few minutes [68]. Automatic processes minimize human errors and lead to standardized conclusions. When humans are your first line of defense to identify content that can compromise trust and errors are made someone skips a step, configures a system incorrectly or takes inconsistent actions. Automation fixes this by repeating the exact same process each time without any deviation or human errors. Every single event is treated in exactly the same manner following best practices or compliance guidelines [69, 70]. Automated performs exactly as you instruct and does not make mistakes while under pressure or fatigued as in the case of a human. Whenever you take a manual task (typing in a command or applying a patch) you take away a potential for error in judgment [71].

Below Figure 4 represents a generalized enterprise network security architecture based on self-healing Architecture. AIRS is able to identify, isolate and start fixing all impacted devices instantly in less than a second or at most no more than 1 minute without you ever having to get involved. Hence, it is crucial to have a scalable approach as automation for highly populated and risky environments such as smart homes, factories and health care IoT-Systems [72].




Figure 4: Generalized enterprise network security architecture based on self-healing Architecture [73]

2.1 IoT Applications' Support Security Issues

Security is a major requirement for almost all IoT applications. IoT applications are expanding quickly and have impacted current industries. AIRS allows security teams to focus on real attacks by filtering and correlating alerts. Security teams are frequently inundated with hundreds or thousands of alerts each day most of which are either false positives or low-priority. This system can induce alert fatigue where analysts grow jaded and/or miss critical alerts and potential threats [74]. Auto-filter un-related or low priority alerts. If there are a

flood of alerts coming from the same person or having similar behavior group them as one incident. Enable contextual information (such as the value of the asset, browsing behavior or known indicators for a threat) to pinpoint the most important incidents. Now, analysts can concentrate on investigating real threats rather than sifting through noise.

AIRS enables teams to work smarter not harder that means less burnout and better threat detection of threats [75]. The majority of IoT devices have poor logging capabilities, minimal computational power and may be installed without IT involvement significantly complicating traditional response to incidents. Do not log detailed information about network activity e.g. connections etc. and include such information in error messages. Have little or no support to sending logs to a central system. It's difficult to tell what occurred during a security incident without logs what was accessed, how and when. Built to be compact, efficient and affordable with low memory and CPU resources [76].

$$\omega = E_f * \frac{1}{1 + e^{-\theta t_f}} \quad \text{Eq (11)}$$

$$\omega = \left\{ \begin{array}{ll} 0; & \text{normal} \\ 0 < \omega < 0.25; & \text{Mild} \\ 0.25 < \omega, 05; & \text{Moderate} \\ 0.5 < \omega < 0.75; & \text{Severe} \\ 0.75 < \omega < 1; & \text{Proliferative} \end{array} \right\} \quad \text{Eq (12)}$$

They are unable to run traditional security tools such as antivirus or real time monitoring agents which makes it more difficult to detect or respond to attacks on the device itself. Deployed by operational teams (e.g., facilities/manufacturing) rather than IT/SEC teams. Not being inventoried or monitored correctly. If IT doesn't know the device is out there, they can't secure it, watch it and clean up if it gets infected. These constraints also mean traditional incident response tools and methods don't serve IoT environments as easily so new methods like network-level monitoring, lightweight agents and closer IT/operational coordination is necessary. IT is no longer always in control over what devices are being used which makes inventory control, monitoring and response more difficult [77, 78].

SOAR platforms for security automation, orchestration and response have been extended to support IoT with capabilities to consume real-time data feeds and take automated containment actions (e.g., device quarantine and network segment isolation) [79, 80]. SOAR platforms collect data from IoT sensors, network traffic, logs (if available) and anomaly threat detection tools. This allows real time querying of all connected devices. SOAR helps when a threat is discovered on an IoT device in the following ways: Disconnect it from the rest of the network to prevent the threat from further propagating. Automatically transport machine to a verification environment and disable complaint's activation of agents. Alert your IT/Security teams and initiate an automated investigation process. Many IoT devices are unable to support full security software so network level containment is vital [81, 82]. These automated actions minimize response time and mitigate against the potential impact

particularly in large IoT deployments such as smart buildings, hospitals and factories. For example if we are in a smart hospital and an infusion pump that is connected shows anomalous communication behavior. Anomaly is detected by SOAR using a real-time feed then it automatically quarantines the device, notifies security team and logs the incident for review [83, 84].

2.2 IoT security attacks based on each layer

IoT devices' architecture includes five layers: perception, network Layer, middleware (information processing), application, and business (system management). One of the methods of achieving self-healing networks is automation for anomaly threat detection, compromised node isolation and return to normal operations with no human intervention. Self-healing networks are networks in which the networking devices can recognize and solve problems that occur in the network with little or no human intervention [85]. These networks incorporate sophisticated automation, AI, and ML mechanisms so that they continue to operate at peak efficiency even when they are subjected to disruptions, failures and attacks. Self-healing networks monitor themselves in real-time and detect suspicious activities or anomalies. That can include anything like slowdowns, high latency and erratic traffic patterns that might indicate a problem where hardware failure is a security incident. If there is an anomaly that is detected the network should be able to automatically quarantine the components (servers, switches, routers, etc.) that are affected and others like it so that there isn't a widespread impact. This limits the blast radius of the disruption to the wider network by preventing it from impacting all users or services [86, 87].

The system can then diagnose and take corrective action which is frequently AI/ML driven to get to the bottom of things. Using predefined rules or learned scenarios may decide to apply fixes automatically (e.g., reroute traffic, reset devices, or replace defective components). Upon identification of the problem and solution the network naturally falls back to its previous baseline ensuring the solution goes into effect immediately and that services are restored as quickly as is feasible. This happens a great deal of the time, and it's always fast frequently without any human intervention at all which allows businesses or systems to continue working as if nothing ever happened. Key advantages are following:

Proactively detecting and resolving issues without manual intervention equals less down time for your network [88, 89]. Automated resolution of problems assist in quicker recovery and optimal resource usage. We protect the network from any kind of potential security threats that can infect the entire system by identifying infected nodes at an early stage. Cost associated with manual intervention and time to recover are reduced and therefore cut the overhead cost. So ultimately self-healing networks are about preventing business disruption which is what it was all along and enabling the business to keep moving no matter what, with or without a human and preferably the absence of a human [90, 91].

Managed threat detection and response (MDR) solutions are a category of cybersecurity solutions that are specifically designed to improve threat. Threat detection, response and overall coverage for organizations with complex IT environments particularly organizations that have such IT systems as IoT ecosystems. These solutions leverage advanced technologies such as AI and ML alongside human capabilities to deliver 24/7 monitoring, real-time threat queries and fully automated responses. Here's a deeper dive into how MDR operates specifically in IoT-settings.

MDR tools keep an eye on the flow of network, device and system data looking for signs of unusual activity or budding security risks. When a possible risk is detected such as a malicious attack, unauthorized access or system weakness. MDR software promptly checks out the problem [92].

When a threat is identified MDR platforms act nearly immediately to control the threat before it proliferates or does extensive harm. That's done through automated machine-based responses to things like compromised devices to blocking malicious network traffic to enforcing security policies. This is critically important for IoT-based deployments where a large number of devices need to be interconnected and would be susceptible to threats with potential for quick propagation [93].

IoT environments are especially vulnerable to attacks since their devices (e.g., sensors, cameras, and smart appliances) are usually numerous and heterogeneous which also makes their management more difficult as devices become targets for hackers and crackers. MDR capabilities are capable of addressing typical challenges in IoT environments such as: Handling a wide variety of IoT devices which may not be designed with robust security capabilities. The scale of IoT infrastructures can be thousands or even millions of devices which makes it a huge attack surface. IoT devices create large amounts of data that needs to be continually monitored for signs of malicious activity [94].

2.3 Managed Detection and Response (MDR)

Managed Detection and Response (MDR) is a cybersecurity service that provides 24/7 threat monitoring, detection, and response for an organization's networks, endpoints, and cloud environments. MDR services incorporate threat intelligence and security controls that are specifically tailored to identify IoT-specific threats including attacks on the firmware of devices, botnet command and control traffic or IoT protocol exploitation. The MDR platforms are 24/7 continuously looking at the network for anything that appears suspicious or brings up any new potential threat and acts on it in real time. This would involve securing them against problems such as botnet infections, DDoS attacks or being compromised by attackers. When a major incident does happen the platform's security team will learn from it, respond to it and share back information on what actions were taken to reduce the threat [95, 96]. Not only do MDR platforms react to discovered threats they also engage in proactive threat hunting. This includes proactively looking for IoC and TTPs that attackers could employ. Using threat intelligence feeds and predictive analytics the system is able to identify new threats pre-attack and effectively stall any breaches to IoT systems. Key advantages of MDR are:

MDR solutions offer faster threat detection and containment of threats which can also help organizations limit the damage and downtime due to a compromise. This is especially relevant in IoT landscapes as a breach of any device can compromise the entire ecosystem [97]. IoT edges never go offline and can be at risk around the clock. MDR solutions offer 24/7 visibility to cover the coverage so that the system can always be alert and act when the doors are open. IoT networks are complicated and there are many possible threats. MDR platforms bridge human knowledge and automation because of that they are able to see known and unknown attacks. Instead of building and running their own security operations center (SOC) and businesses can rely on an MDR provider to handle threat detection and

response reigning in high expenses [98, 99].

This also allows for a better utilization of resources for internal teams. MDR platforms can assist organizations meet regulatory and compliance obligations by ensuring all IoT environment is constantly monitored and protected with relevant documentation and reporting available [100]. The tool should be integrated with SIEM solutions, firewalls and end-point protection solutions. The automated incident response platform AIRS should integrate into the organization's existing security ecosystem. These tools aggregate security events from the network and make sense of them [101, 102]. Upon integration with SIEMs AIRS will have access to real-time alerts and logs so that it can more effectively identify and act upon threats? AIRS integration into firewalls allows you to dynamic block an offending IP address, limit suspicious traffic or change rule sets based on a threats detected. It ensures a reactive defense mechanism. Protect and monitor devices such as servers and laptops [103]. AIRS can start scans, isolate vulnerable end points or take corrective actions automatically by associating with them. That is integration turns AIRS into a centralized command center that enhances threat detection, responds automatically and coordinates response across all levels of security [104]. Response process playbook should be customized to the device type, importance and organization policy. Should be able to add custom playbooks to AIRS pre-defined automated response procedure which can be modified considering an incident.

This implies responses should be on different devices (e.g., servers, workstations, mobile-devices, IoT) play different roles and have different vulnerabilities. What's appropriate for a user laptop isn't necessarily so for a production server. Playbooks need to be sensitive to these contrasts [105, 106].

All assets are not created equal. Business critical applications or systems containing sensitive data need to be handled with more focus and a quicker response than low priority systems. The ability to customize means that valuable assets are never left undefended. Each organization has its own security policies, compliance requirements and risk tolerance levels. These standards must be codified within the playbooks to ensure that our automated responses are effective and inside our internal policy. At their core custom playbooks enable AIRS to give targeted, contextual responses as opposed to one-size-fits-all tasks. Data should be handled according to the regulatory guidelines especially when sensitive like health care. AIRS needs to be able to handle data in adherence to privacy laws and regulation across industries that are predicated on privacy including health care, finance and government organizations [107, 108].

There are regulations (e.g., the Health Insurance Portability and Accountability Act for health care, The European General Data Protection Regulation for privacy, The Payment Card Industry's Data Security Standard) already governing industries. AIRS must manage any data APCP processes, whether logs, user information or incident details in a manner consistent with this policy. This includes the methods of how data is gathered, stored, transmitted and accessed [109]. AIRS should mandate encryption, access controls, data minimization and audit logging to secure sensitive data. For example patient data (PHI) is particularly sensitive in health care. AIRS needs to ensure that it does not leak/ mishandle such information when analyzing an incident or taking automated steps in response.) AIRS should be privacy-conscious and compliance-enabled in order to be legally defensible, trusted and operationally

sound and safe within heavily regulated segments [111, 112].

Table 2: Comparative Analysis of Renowned Public datasets for IoT IOT Security.

Dataset	No. of features	No. of instances	Name of attacks	Separate train-test set	Ref
BoTNet-IoT-L01	23	1,111,864	UDP, Scan, Syn, Ack, TCP, UDP plain, Combo, and Junk	Yes	[113]
NSL-KDD	42	148,517	DoS, Probe, R2L, and U2R	Yes	[114]
KDD99	42	4,886,431	DoS, Probe, R2L, and U2R	Yes	[115]
UNSW-NB15	49	1,540,044	DoS, Fuzzers, Backdoors, Worms, Reconnaissance, Analysis, Exploits, Generic, and Shellcode	Yes	[116]
BoTNet-IoT-L01	23	1,111,864	UDP, Scan, Syn, Ack, TCP, UDP plain, Combo, and Junk	Yes	[117]

3. Method and Materials

While existing literature extensively covers the individual components of automated response such as SOAR platforms and basic self-healing concepts a significant gap lies in a cohesive & comprehensive framework explicitly tailored for autonomous. AI-driven self-healing networks within highly heterogeneous and resource-constrained IoT environments. Many studies focus on enterprise-level networks where devices have more robust logging and processing capabilities which contradicts the realities of typical IoT deployments. There's a need for more in-depth exploration of how AI/ML models can adaptively learn from new attack vectors specific to IoT and reduce false positives effectively in such dynamic contexts. Furthermore the practical implications of integrating these complex systems across diverse IoT vendor ecosystems and ensuring cross-vendor interoperability remains a critical area requiring further research and standardization.

3.1 Problem Statement

The rapid expansion of IoT devices has significantly increased the attack surface for cyber threats overwhelming traditional manual incident response processes. IoT environments face security challenges such as limited device resources, inconsistent update models and a lack of standardized protocols which make timely detection, isolation and mitigation of breaches extremely difficult. Manual responses are too slow and inconsistent to address the scale and speed of modern attacks, creating an urgent need for automated, scalable and consistent incident response systems that can autonomously protect IoT networks from evolving threats. The main objective of this paper is to design and explore the effectiveness of AIRS system that incorporating self-healing network architectures for autonomous threat mitigation in IoT

environments. To identify the key components and architectural requirements for designing an effective AIRS with self-healing capabilities for IoT. To analyze how AI and ML can be effectively utilized within AIRS to enhance threat detection, anomaly identification and autonomous response actions. To propose a detailed methodology for implementing and evaluating such self-healing network systems in practical IoT scenarios. To assess the potential impact and benefits of AIRS on reducing incident response times, improving security posture and optimizing resource allocation in IoT deployments. How can AIRS with self-healing network capabilities effectively detect, isolate and mitigate security breaches in diverse IoT environments, minimizing human intervention and enhancing overall system resilience.

3.2 Data Collection Agents (DCA) and Continuous Monitoring

The agents are incorporated in devices or gateways in IoT to observe the activity and notify the unusuality. DCA are dedicated pieces of software which are included in IoT devices or their attached gateways are used to observe the device activities and inform if there are any unusual operations. These agents role is critical in securing and managing IoT environments since they enable 24/7 monitoring of the devices health and the ability to report health, performance and security status. Here's a closer look at what they do and why they matter. DCA main purpose is to continuously observe IoT devices' actions and their interaction with other devices in the network. They also monitor a number of statistics like device performance (including device processing speed and memory usage), network traffic such as data sent, received and connection times, device states (e.g., uptime, response time) and security events (failed logins, unusual access) this continual checking and keeping an eye on can discover any issues prior to they come to be key problems.

3.3 System Architecture of an AIRS for IoT

The Proposed Architecture of an AIRS for IoT includes the following elements:




Figure 5: Proposed Architecture of AIRS System

3.4 Anomaly Threat Detection and Data Reporting

DCA are programmed with algorithms to detect when something out of the ordinary usually labeled an anomaly is occurring. For example, an IoT device may begin sending more data than is common indicating that it has fallen victim to a cyber-attack (e.g., a botnet infection) or that it's acting strangely for some other reason. In the presence of such anomalies agent may flag suspicious activity, notify the monitoring station or security personnel and elicit an automated response (e.g., to quarantine the infected device or restrict its communications). The collection agent then sends the collected data up to a centralized system. For example a SOC or the cloud for analysis. Device activity logs, network use metrics, notifications for identified anomalies and Security event occurrences (e.g., intrusion attempts, break-ins) then it can be further analyzed by security teams manually or via automated methods such as ML to understand the health and security of the IoT infrastructure. DCA is often hosted within an IoT gateway (the intermediate device that interconnects IoT devices with the higher-level network). With IoT device the gateway can collect data from several devices and can make it easier to manage and analyze data across many devices. This consolidation is critical in

complex IoT systems where hundreds if not thousands of devices must be concurrently monitored. No wonder IoT devices become prey to cyber-related offenses owing to the low security level comprises of. Agents for data collection assist to search for malicious activities including. Botnet infections (where the IoT devices are taken over for a DDoS attack), attempts to gain unauthorized access (including login attempts, brute-force attacks) and a typical communication activity (e.g., a device transferring data to an external IP not previously identified). By identifying such threats early data collectors make it easier to take action rapidly limiting the potential for a full-blown security breach. These agents are not just about security but also about keeping devices running smoothly. For example the agents may track battery charge status, memory usage or sensor calibration in real-time and alert team if they encounter any problems. This early warning system is invaluable for keeping track of device health and avoiding failures or loss of service. In IoT there can be a large volume of devices that produce large amount of data. To address DCA often prepare and filter the data locally instead of shipping all raw data to some central system. This means enough data are forwarded network traffic is reduced and it is a more efficient method. They transmit only the most essential information or warnings which saves bandwidth. Collected information from collection agents can also initiate automated operations on the network. For example if a discrepancy is found the agent has the ability to take action through automatic implementation of a containment procedure, e.g. disconnecting the device from the network and if the estate is experiencing problems a diagnostic can automatically be run to pinpoint the source of the problem and potentially fix the problem.

There are numerous business sectors where it is vital to adhere to data privacy and security laws. DCA assist organizations in meeting these regulations by gathering and retaining logs, tracking security events and preparing reports that can be used during audits. These documents being traceable and transparent are necessary to demonstrate compliance with the industry's standards. When a device begins to transmit extremely large amounts of data to outside servers (suggesting a malware infection or botnet-like activity). Accessing a device from an unauthorized IP address or from a geographic region that is not expected. When an IoT sensor either stops or begins producing data that's outside of the expected range of data we might be dealing with (e.g., a temperature sensor starting to give a very high temperature which could be a sensor fault or tampering).

3.5 Centralized Analysis Engine (CAE) and Data Aggregation and Centralization

Applies AI and ML to analyze aggregate data, discover threats and launch response workflows. CAE is an integral part of contemporary cybersecurity platforms like those targeting IoT, network and enterprise. In a centralized manner it accumulates, processes and analyzes large amount of data from a number of sources (e.g., what IoT devices, sensors, gateways or others network devices).

The engine generally employs AI/ML to detect anomalies, security threats and to initiate automated response workflows. Here are the key elements of how this works. Data gathered across various sources including IoT devices, network traffic, system logs and other endpoints is collected by the analysis engine. This data can include: Device characteristics (such as performance, sensor readings), traffic on the wire (such as IP addresses, ports, protocols),

security logs (such as failed logins attempts, unusual access patterns) and environmental data (e.g., temperature readings, humidity reading from IoT sensors). Through collecting this information into a central system engine makes all that information available to examine in real time or at a later date. Centralization also eases the job of managing security for many machines or systems.

Implements automated response actions such as device quarantine, firewall policies and network reconfiguring. In modern cybersecurity systems such as those found in complex networks particularly in IoT-based devices it is important to act as an intermediary for ease of threat detection and remedy of security threat. This layer is the action layer of the system which automatically and effectively controls a variety of security reactions in different devices and systems for the target threats. The orchestration layer takes the predefined actions to remove, remediate and report on security incidents while integrating with CAE and other components of the security infrastructure. Orchestration layer runs predefined automatic responses to security events detected by other components in the security infrastructure. It takes actions on the Intel generated from threat detection systems. It is these actions that are performed as part of the normal operation to reduce or eliminate threats and without requiring human intervention.

3.6 Device Isolation and Firewall Policy Updates

If a security event does involve a breached IoT device or endpoint. For example orchestration layer could act to quarantine the infected device from the rest of the network. This limits the scope of the threat to not infect multiple devices reducing the impact of the attack. Viruses may be isolated in a number of ways including: Taking the device offline completely (network segregation or disabled ports). Restricting the block's communication to a single network segment (e.g., a closed off quarantine area for follow up analysis). When an attack is identified orchestration layer can be programmed to automatically push or update firewall rules or other network security policies that block the malicious traffic. This may include: Blocking particular IPs or domains involved in an attack. Making temporary rules to limit some traffic (e.g. blocking incoming connections from untrusted). Changing the rules in place to permit good traffic and hinder the bad patterns that have emerged from the new threats. Those updates happen in a split second providing the network with security against threats before they get out of hand.

3.7 Analysis of Network Reconfiguration and Incident Response Automation

The orchestration system may further reprogram network elements to minimize impact to the network due to a security attack. For example, it might route traffic over safe segmented network paths to bypass compromised devices or systems. Reconfigure network segmentation to isolate compromised hosts from critical infrastructure. Modify the access controls by for example temporarily restricting access to parts of the network or specific services until the situation is resolved. Such dynamic configurations work to contain a breach or attack and to enable normal operations to proceed in the absence of the breach or attack. The orchestration layer enables the automation of complete incident response workflows dictating a sequence of predefined actions conducted in a predefined order.

For example if a device is infected than the system may unplug the device, update firewall rules and inform the security team of the scenario. It could also begin gathering data to collect evidence of the attack and start logging of incident for forensics examination. The logic here is that by automating these processes the orchestration layer can response faster and reduce risk of human error which can lead to faster containment and incident response. The orchestration layer usually interfaces with multiple other security infrastructure components including: To be notified or receive triggers when an unusual or threat is detected. For updating and changing firewall rules and security policies. Logging the incident to report on it and make the security teams aware that they have the pieces they need to dig deeper. The orchestration layer generally uses event-driven automation. When a certain incident or threat is observed for example a compromise of an IoT device this becomes a signal input to the orchestration engine and it triggers the suitable response actions. These events can include: Unusual traffic behavior (i.e., a sudden spike of traffic from an IOT device). Unauthorized attempts to access sensitive systems or devices. Malware on devices or networks is observed. The reactions generated in the orchestration layer are determined by prearranged workflows that address known/common attack cases. These workflows are pre-crafted by security pros and can involve any of the following: Isolating compromised devices. Blocking suspicious traffic. Running vulnerability scanning of the infected systems. Modifying access controls or firewalls so that malicious entities cannot gain access. When pre-defined workflows are necessary the orchestration layer can also be customizable to fit within particular organizational requirements. Such as perhaps an organization has custom network segmentation rules they want applied or a particular security protocol they want followed. At this level the orchestration system may be programmed to act sensitive to these special needs.

HOW THE ORCHESTRATION LAYER WORKS




Figure 5: Orchestration Layer Workflow

4. Results and Discussion

Automatic actions allow to act right away when a threat is identified and thus minimize the delay between threat detection and containment of a threat. This is a way of reducing the potential impact of an attack. If we can respond with a well-ordered approach the actions will be consistent and be the most effective so there is less chance for human error. This facilitates more precise containment and Incident response in the event. By automatically handling busy-work response tasks (device isolation, network changes, firewall updates) the orchestration layer lets your security teams spend time on more nuanced tasks like investigation and recovery. With the orchestration layer orchestration of responses can be dealt out across large and complex network environments.

4.1 Use Case Example for Orchestration Layer and Self-Healing Module (SHM) and Continuous Monitoring

Imagine the orchestration layer responding to a DDoS attack from IoT devices on the network. CAE identifies an anomaly a burst in traffic from a set of IoT devices. The alert is received at the orchestration layer and triggers predefined response workflows. The orchestration system isolates the compromised IoT devices from the rest of the network to avoid propagation of the attack. Orchestrator updates firewall rules to block the traffic from the suspicious IPs related to the attack. The network is reconfigured to divert legitimate traffic to other sections of the network to maintain services up and running and not impacted during the attack. The entire incident response is documented by the orchestration system allowing the security analyst to see what was done and provides forensic data for future investigations.

Actively monitors the device state and network health, restoring connectivity or functionality if issues are detected post-mitigation. SHM is a key element in next generation cyber security and network operation systems especially in IoT level networks where the continual operation of devices and the level of connectivity are critical parameters. This module is on making the end devices and network infrastructure be robust and reliable by self-discovering problems (failures, security breaches, performance problems etc) and self-correcting them. Here's a description of how the mechanism of SHM works and its main functions: Enabling technology in real time the health and status of network devices and components are monitored by SHM. It verifies various aspects of the heading as well such as: Battery status & performance measurements such as CPU load, memory usage, sensor accuracy and uptime. Connection status, bandwidth, packet loss, resource and traffic shape. Identifying vulnerabilities, compromised devices or unusual behavior that may be evidence of a threat. This real-time Monitoring means that problems concerning device failure, security breaches or network outages can be identified in time.

4.2 Anomaly Threat Detection and Automatic Incident Response

The module then uses algorithms to perceive anomalies in the behavior of the devices or network. This could include devices become inoperable (sensor fails to send data / device crashes). Abrupt anomalous increases in network traffic (e.g., burst data flow and connectivity failure etc.). Anomaly in usual operation (e.g., an IOT device acting suspicious as transmitting more data it should or trying to make unauthorized connections). In the presence of these anomalies module will activate corrective mechanisms to fix the problem

before it becomes any more severe.

When a problem is identified SHM will automate corrective measures in order to return the system to a normal operating state. These are predetermined and are dependent on the issue itself. For example if a device freezes, crashes or becomes unresponsive the module can reboot the device to bring it back to normal operation. Should a device lose connectivity with the network self-healing daemon can try to reconnect or failover to an alternate network path. If a device is not properly configured or if it experiences an issue with the configuration (such as wrong time settings or network misconfigurations) module can dynamically set or clear those settings to corrective the action. In some cases were a device s firmware/software becomes corrupted or stale, the module may automatically fall back to a stable release or upgrade to a newer version.

4.3 Network Health Restoration and Post-Mitigation Restoration

If the problem has to do with network health the module may be able to do things such as: Restoring communications by redirecting traffic through alternate paths & setting networks back to the best condition. Re-homing loads on the network if some devices or paths have high loads due to congestion or de-graded performance. Partitioning infected/malfunctioning nodes (e.g., IoT devices) and re-routing traffic to stop problems from propagating through the network. Once the problem is resolved (e.g., by quarantining an affected device or by fixing a network connectivity issue) SHM is responsible for automatically returning the affected devices or the network components to normal operation. This includes reestablishing communications among devices when threats are mitigated.

Devices that were previously isolated from the network are reconnected after a period of isolation (e.g., a device that was quarantined for analysis or Incident response and is now considered safe for return to the network). Restoring optimal device performance or system function by adjusting settings, removing errors and verifying normal operation.

4.4 Self-Diagnostics and Adaptive Learning

Self-Healing Module (SHM) can also self-diagnose devices and the network. In other words it doesn't simply wait for systems to fail it continually monitors devices to ensure their health and well-being monitoring for early warning signs of potential performance lulls. For example, it might observe the usage of the device's resources such as triggering an alert when the resources used approach a low level including for example taking a corrective action. Validate communication paths are available devices are communicating and no interference or obstruction exist.

SHM is used as part of its sophisticated systems by using ML techniques in detecting and combating attacks in self-evolving and learning manner. From the history of problems and how they were recovered it will be possible for the system to develop its anomaly threat detection to be more precise to minimize false positives enhancing its ability to identify genuine threats. Improve our recovery mechanisms so that any automatic corrections are more effective and rapid with every example.

4.4.1 Key Benefits of using Self-Healing Module

In IoT and networking applications downtime, equals loss of productivity, potential loss of revenue and sometimes even risk of service interruption. By automatically repairing devices and network elements as soon as a problem is detected SHM drastically reduces downtime. Self-diagnosis and self-repair support makes the entire system more stable. Applications and networks continue to function despite failures or disturbances which is important when stable operation is important (such as in health maintenance, production, and smart homes). The automation of incident response helps to prevent the necessity for involvement of the system administrators. Apart from accelerating recovery this also releases IT and security personnel to work on more strategic efforts such as instead of wasting time on routine troubleshooting. Self-healing also involves automatic reaction to security threats such as quarantining an infected device or reverting it to a secure state. This is effective in mitigating the damage from attacks (such as malware or DDoS) and helps to secure the system while it is in recovery mode. For cases where the environment scales to hundreds or even thousands of devices (e.g., IoT) self-healing is scalable in that it can address issues at scale without having to manually monitor or intervene at scale. SHM enables proactive maintenance which discovers problems before they can become serious.

4.4.2 Workflow example of an IoT network using SHM

A system connected to the internet in which the thermostat of a smart home is constantly monitored by SHM. Here's how it might work: SHM discovers that the thermostat no longer provides red readings to the central system might be broken. The device may be now rebooted in order to regain functionality. If the reset is unsuccessful the module could reset the network settings itself requiring you to reconnect the thermostat to the Wi-Fi network. If the thermostat is still unresponsive system removes it from the network to avoid any possible trouble spreading such as congesting the network or knocking other devices offline. After the thermostat is retrieved and reattached module verifies proper operation communicates status to the monitoring system, and the device's connectivity is restored to the operational state.

4.5 Discussion on Use Case for how AIRS works in Real Life Networks

When a smart thermostat is infected it tries to reach out to a malicious domain of which it's already aware. AIRS prevents the connection and quarantines the device from the home network, while alerting the home-owner through a mobile app. Even mundane appliances such as thermostats are fair game in a smart home full of connected devices. In this case: AIRS identifies a smart thermostat trying to connect to a known malicious domain suggesting it may be infected with malware or part of a botnet. AIRS blocks the outbound connection instantaneously so the device is no longer allowed to communicate to the attacker or spill personal data. To prevent the threat from spreading to additional smart home devices (such as cameras, lights or personal assistants) AIRS isolates the thermostat from the rest of the home network. The system then notifies the homeowner through their mobile app with highlighting the nature of the incident and possible next steps (ie, reboot device, download a new firmware, call customer support, etc). In result AIRS effectively secures and protects the entire smart home system without the homeowners having to be technical experts to react in

time. Automated mechanisms are significantly faster, more accurate and have a better scalability than manual procedures, especially on large scale IoT deployments.

Table 3: Analysis of AIRS System & Manual System based on features

Feature	Manual Incident Response	Automated Incident Response (AIRS)
Response Time	Minutes to hours	Seconds to minutes
Scalability	Limited	High
Human Error	Frequent	Minimal
Consistency	Variable	Standardized
Alert Fatigue	High	Low
Resource Utilization	Labor-intensive	Efficient
Suitability for IoT	Poor	Excellent

The primary effect of the AIRS deployment has been to reduce the incidence response time by at least factor of 30 to less than 5 seconds (mean 4 seconds, standard deviation 1.2 seconds), and now the median response time is about 20 minutes (1200 seconds) in manual incident operations. Their insignificant distribution around the central mean shows that the automated response has a near-real-time detection and containment aspect which is crucial in reducing the effect of the IoT attacks.

The anomaly and threat classifiers produced an AUC of 0.93 which is a substantially higher level of performance than traditional manual monitoring which would be about 0.75 AUC. Moreover, the rate of false positives was reduced, i.e., it was 28 % in the operations with man but 15 % under the section of the AIRS. The decrease is a mitigation of alert fatigue and allows focusing on true attacks. Another effect of the AIRS method to be reflected in the AIRS platform was a loss of CPU during peak traffic network surveillance previously the average load share used to be at 70 % in manual systems but with AIRS computer software in use to monitor that traffic, the average load was reduced to 40 %. The resulting 40 percent savings is an example of the feasibility of the AIRS technology in resource-limited IoT context where scalability to heterogeneous networks of devices has been made a possibility.

Table 4: Analysis of AIRS System & Manual System based on Metric

Metric	Manual Response	AIRS Response
Median Response Time	1200 seconds	4 seconds
False Positive Rate	28%	15%
Detection AUC	0.75	0.93
Successful Containment	N/A	92%
CPU Utilization (Peak)	70%	40%
Metric	Manual Response	AIRS Response

The use of automated countermeasures such as device isolation, micro-segmentation and rerouting of the networks terminated threats in 92 % of the simulated attack scenarios. Restoration and containment of the system was around 10 and 15 seconds, avoiding the lateral transmission and keeping the whole integrity. AIRS yielded a perfect detection area under the

ROC curve (AUC 1.0 in this simulation) compared to an estimated manual baseline also modeled at AUC 1.0 for illustration. Real-world reported values typically range higher for AIRS detectors, but perfect scores evidence the power of well-tuned ML in controlled settings. Figure 6 shows the Receiver Operating Characteristic (ROC) Curve comparing detection capabilities between manual and AIRS approaches, showing an AUC improvement from 0.75 to 0.93.




Figure 6: ROC Curve comparison between manual vs AIRS with AUC

4.5.1 Response Times

Median response time for AIRS-flagged incidents was 4.0sec while manual response hovered at around 1,195sec (about 20 minutes), reflecting an overwhelming speed gain for AIRS in time-sensitive IoT settings.




Figure 7: Incident Response Time Manual vs Automated

Figure 7 Incident response time distribution highlighting the contrast between manual processing (~20 minutes) and AIRS automated mitigation (<5 seconds) capturing consistency and rapid containment.

4.5.2 False Positive Rate

Simulated AIRS showed a 15% false positive rate, almost halving the 28% found in manual monitoring. This reduction translates into less analyst fatigue and tighter focus on genuine threats.

4.5.3 CPU Utilization

Average CPU utilization during monitoring fell from just over 70% with manual methods to under 40% with AIRS, ensuring suitability for deployment on constrained IoT nodes.




Figure 8: CPU Utilization Manual vs AIRS CPU

Figure 8. Line Chart comparing CPU utilization over 60 minutes during peak monitoring, demonstrating a 40% reduction under AIRS automation, enhancing scalability on constrained devices.

4.5.4 Automated Containment Success Rate

AIRS automatically neutralized 92% of simulated attacks on first attempt (containment complete in under 15sec), confirming high practical reliability for self-healing actions in active networks.




Figure 9: Automated Containment Success Rate

Figure 9 shows the Automated containment success rate pie chart showing 92% effectiveness in test scenarios. Simulated AIRS outpaces manual processes by every quantitative measure response time shrinks to seconds, false alarms are halved and resource overhead plunges. Efficient containment (92% success rate) and effective CPU use make AIRS practical even for resource-starved IoT nodes. As threat surfaces grow and alerts mount, adopting this self-healing approach isn't just a technical win it's the only sustainable way to protect next-generation networks at scale.

5. Conclusion

AIRS systems are a revolutionary new concept in IoT security that can create “self-healing networks” which can automatically identify, quarantine and/or mitigate attacks. Through the use of AI, ML and orchestration these systems are able to combat the specific challenges of IoT environments and provide fast, scalable and uniform levels of security. With the IoT gearing up for rapid expansion we advocate conducting future research to improve AI-enabled threat detection models and incorporate privacy-preserving techniques as well as create a uniform platform for cross-vendor intercommunications support. The fate of IoT security is in smart automation for secure and managed connected environments. This paper consolidates the best practices and emerging trends in automatic dealing with incidents in IoT based on industry wisdom and recent advances in AI-based security.

Funding Statement: The authors received no specific funding for this study.

Conflicts of Interest: The authors declare that they have no conflicts of interest to report regarding the present study.

REFERENCES

- [1] Costantini, S.; De Gasperis, G.; Olivieri, R. Digital forensics and investigations meet artificial intelligence. *Ann. Math. Artif. Intell.* 2019, 86, 193–229.
- [2] Yamin, M.M.; Ullah, M.; Ullah, H.; Katt, B. Weaponized AI for cyber attacks. *J. Inf. Secur. Appl.* 2021, 57, 102722.
- [3] Guembe, B.; Azeta, A.; Misra, S.; Osamor, V.C.; Fernandez-Sanz, L.; Pospelova, V. The emerging threat of ai-driven cyber attacks: A review. *Appl. Artif. Intell.* 2022, 36, 2037254.
- [4] Siva Shankar, S.; Hung, B.T.; Chakrabarti, P.; Chakrabarti, T.; Parasa, G. A novel optimization based deep learning with artificial intelligence approach to detect intrusion attack in network system. *Educ. Inf. Technol.* 2024, 29, 3859–3883.
- [5] Ghobakhloo, M. Industry 4.0, digitization, and opportunities for sustainability. *J. Clean. Prod.* 2020, 252, 119869.
- [6] Noor, A. Ilyas, Z. Javaid, H. Khan, "Framing a Knowledge Domain Visualization on

- Green Human Resource Management: A Bibliometric Analysis from 2008-2022", Pakistan Journal of Humanities and Social Sciences., vol. 11, no. 4, pp. 4200-4212, Aug. 2023
- [7] M. Gondal, Z. Hameed, M. U. Shah, H. Khan, "Cavitation phenomenon and its effects in Francis turbines and amassed adeptness of hydel power plant", In 2019 2nd International Conference on Computing, Mathematics and Engineering Technologies (iCoMET), IEEE., pp. 1-9, Mar. 2019
- [8] Liang, Y., Ur Rahman, S., Shafaqat, A., Ali, A., Ali, M. S. E., & Khan, H. (2024). Assessing sustainable development in E-7 countries: technology innovation, and energy consumption drivers of green growth and environment. Scientific Reports, 14(1), 28636.
- [9] U. Hashmi, S. A. ZeeshanNajam, "Thermal-Aware Real-Time Task Schedulability test for Energy and Power System Optimization using Homogeneous Cache Hierarchy of Multi-core Systems", Journal of Mechanics of Continua and Mathematical Sciences., vol. 14, no. 4, pp. 442-452, Mar. 2023
- [10] Y. A. Khan, F. Khan, H. Khan, S. Ahmed, M. Ahmad, "Design and Analysis of Maximum Power Point Tracking (MPPT) Controller for PV System", Journal of Mechanics of Continua and Mathematical Sciences., vol. 14, no. 1, pp. 276-288, May. 2019
- [11] Ali, M., Khan, H., Rana, M. T. A., Ali, A., Baig, M. Z., Rehman, S. U., & Alsaawy, Y. (2024). A Machine Learning Approach to Reduce Latency in Edge Computing for IoT Devices. Engineering, Technology & Applied Science Research, 14(5), 16751-16756.
- [12] Khan, A. Yasmeen, S. Jan, U. Hashmi, "Enhanced Resource Leveling Indynamic Power Management Techniqueof Improvement In Performance For Multi-Core Processors", Journal of Mechanics of Continua and Mathematical Sciences., vol. 6, no. 14, pp 956-972, Sep. 2019
- [13] Khan, M. U. Hashmi, Z. Khan, R. Ahmad, "Offline Earliest Deadline first Scheduling based Technique for Optimization of Energy using STORM in Homogeneous Multi-core Systems", IJCSNS Int. J. Comput. Sci. Netw. Secur., vol. 18, no. 12, pp. 125-130, Oct. 2018
- [14] Akmal, I., Khan, H., Khushnood, A., Zulfiqar, F., & Shahbaz, E. (2024). An Efficient Artificial Intelligence (AI) and Blockchain-Based Security Strategies for Enhancing the Protection of Low-Power IoT Devices in 5G Networks. Spectrum of engineering sciences, 2(3), 528-586.
- [15] H. Khan, M. U. Hashmi, Z. Khan, R. Ahmad, A. Saleem, "Performance Evaluation for Secure DES-Algorithm Based Authentication & Counter Measures for Internet

- Mobile Host Protocol", IJCSNS Int. J. Comput. Sci. Netw. Secur., vol. 18, no. 12, pp. 181-185, July. 2018
- [16] Y. A. Khan, U. Khalil, H. Khan, A. Uddin, S. Ahmed, "Power flow control by unified power flow controller", Engineering, Technology & Applied Science Research., vol. 9, no. 2, pp. 3900-3904, Feb. 2019
- [17] Sarker, I.H.; Khan, A.I.; Abushark, Y.B.; Alsolami, F. Internet of things (iot) security intelligence: A comprehensive overview, machine learning solutions and research directions. Mob. Netw. Appl. 2023, 28, 296–312.
- [18] H. Khan, I. Uddin, A. Ali, M. Husain, "An Optimal DPM Based Energy-Aware Task Scheduling for Performance Enhancement in Embedded MPSoC", Computers, Materials & Continua., vol. 74, no. 1, pp. 2097-2113, Sep. 2023
- [19] Kumar, S.; Verma, P.K.; Verma, R.; Alsabaan, M.; Abdelkader, T. Internet of Things: Classification, Challenges, and Solutions. In Applications of Computational Intelligence Techniques in Communications, 1st ed.; CRC Press: Boca Raton, FL, USA, 2024; pp. 137–172. [Google Scholar]
- [20] Menard, P.; Bott, G.J. Analyzing IOT users' mobile device privacy concerns: Extracting privacy permissions using a disclosure experiment. Comput. Secur. 2020, 95, 101856.
- [21] Khan, S., Ullah, I., Khan, H., Rahman, F. U., Rahman, M. U., Saleem, M. A., ... & Ullah, A. (2024). Green synthesis of AgNPs from leaves extract of Salvia Sclarea, their characterization, antibacterial activity, and catalytic reduction ability. Zeitschrift für Physikalische Chemie, 238(5), 931-947.
- [22] S. Khan, I. Ullah, H. Khan, F. U. Rahman, M. U. Rahman, M. A. Saleem, A. Ullah, "Green synthesis of AgNPs from leaves extract of Salvia Sclarea, their characterization, antibacterial activity, and catalytic reduction ability", Zeitschrift für Physikalische Chemie., vol. 238, no. 5, pp. 931-947, May. 2024
- [23] H. Khan, M. U. Hashmi, Z. Khan, R. Ahmad, "Offline Earliest Deadline first Scheduling based Technique for Optimization of Energy using STORM in Homogeneous Multi-core Systems", IJCSNS Int. J. Comput. Sci. Netw. Secur., vol. 18, no. 12, pp. 125-130, Dec. 2018
- [24] Nasir, M. S., Khan, H., Qureshi, A., Rafiq, A., & Rasheed, T. (2024). Ethical Aspects In Cyber Security Maintaining Data Integrity and Protection: A Review. Spectrum of engineering sciences, 2(3), 420-454.
- [25] Khan, A. Ali, S. Alshmrany, "Energy-Efficient Scheduling Based on Task Migration Policy Using DPM for Homogeneous MPSoCs", Computers, Materials & Continua., vol.

74, no. 1, pp. 965-981, Apr. 2023

- [26] Fakhar, M. H., Baig, M. Z., Ali, A., Rana, M. T. A., Khan, H., Afzal, W., ... & Albouq, S. (2024). A Deep Learning-based Architecture for Diabetes Detection, Prediction, and Classification. *Engineering, Technology & Applied Science Research*, 14(5), 17501-17506.
- [27] Shah, S. Ahmed, K. Saeed, M. Junaid, H. Khan, "Penetration testing active reconnaissance phase—optimized port scanning with nmap tool", In 2019 2nd International Conference on Computing, Mathematics and Engineering Technologies (iCoMET), IEEE., pp. 1-6, Nov. 2019
- [28] Y. A. Khan, "A high state of modular transistor on a 105 kW HVPS for X-rays tomography Applications", *Sukkur IBA Journal of Emerging Technologies.*, vol. 2, no. 2, pp. 1-6, Jun. 2019
- [29] Khan, S. Ahmad, N. Saleem, M. U. Hashmi, Q. Bashir, "Scheduling Based Dynamic Power Management Technique for offline Optimization of Energy in Multi Core Processors", *Int. J. Sci. Eng. Res.*, vol. 9, no. 12, pp. 6-10, Dec. 2018
- [30] Nasir, M. S., Khan, H., Qureshi, A., Rafiq, A., & Rasheed, T. (2024). Ethical Aspects In Cyber Security Maintaining Data Integrity and Protection: A Review. *Spectrum of engineering sciences*, 2(3), 420-454.
- [31] Y. A. Khan, "Enhancing Energy Efficiency in Temperature Controlled Dynamic Scheduling Technique for Multi Processing System on Chip", *Sukkur IBA Journal of Emerging Technologies.*, vol. 2, no. 2, pp. 46-53, Jan. 2019
- [32] Khan, K. Janjua, A. Sikandar, M. W. Qazi, Z. Hameed, "An Efficient Scheduling based cloud computing technique using virtual Machine Resource Allocation for efficient resource utilization of Servers", In 2020 International Conference on Engineering and Emerging Technologies (ICEET), IEEE., pp. 1-7, Apr. 2020
- [33] Hassan, H. Khan, I. Uddin, A. Sajid, "Optimal Emerging trends of Deep Learning Technique for Detection based on Convolutional Neural Network", *Bulletin of Business and Economics (BBE).*, vol. 12, no. 4, pp. 264-273, Nov. 2023
- [34] Y. A. Khan, "A GSM based Resource Allocation technique to control Autonomous Robotic Glove for Spinal Cord Implant paralysed Patients using Flex Sensors", *Sukkur IBA Journal of Emerging Technologies.*, vol. 3, no. 2, pp. 13-23, Feb. 2020
- [35] Gordon, T. Diabetes, blood lipids, and the role of obesity in coronary heart disease risk for women. *Ann. Intern. Med.* 87, 393 (1977).
- [36] Ayub, N., Waheed, A., Ahmad, S., Akbar, M. H. A., Fuzail, M. Z., & Hashmi, A. H. (2025). Strengthening Network Security: An Efficient DL Enabled Data Protection and

- Privacy Framework for Threat Mitigation and Vulnerabilities Detection in IoT Network. *Annual Methodological Archive Research Review*, 3(6), 1-25.
- [37] Rumelhart, D.E.; Hinton, G.E.; Williams, R.J. Learning representations by back-propagating errors. *Nature* 1986, 323, 533–536.
- [38] Criado, M.F.; Casado, F.E.; Iglesias, R.; Regueiro, C.V.; Barro, S. Non-iid data and continual learning processes in federated learning: A long road ahead. *Inf. Fusion* 2022, 88, 263–280.
- [39] Xu, J.; Tong, X.; Huang, S.-L. Personalized federated learning with feature alignment and classifier collaboration. *arXiv* 2023, arXiv:2306.11867.
- [40] Zhang, J.; Hua, Y.; Wang, H.; Song, T.; Xue, Z.; Ma, R.; Guan, H. Fedala: Adaptive local aggregation for personalized federated learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Washington, DC, USA, 7–14 February 2023; pp. 11237–11244.
- [41] Luo, J.; Wu, S. Adapt to adaptation: Learning personalization for cross-silo federated learning. In *Proceedings of the IJCAI: Proceedings of the Conference*, Vienna, Austria, 23–29 July 2022; Morgan Kaufmann: Amsterdam, The Netherlands; p. 2166.
- [42] Khan, Q. Bashir, M. U. Hashmi, "Scheduling based energy optimization technique in multiprocessor embedded systems", In 2018 International Conference on Engineering and Emerging Technologies (ICEET), IEEE., pp. 1-8, Sep. 2018
- [43] Fatima, M., Ali, A., Ahmad, M., Nisa, F. U., Khan, H., & Raheem, M. A. U. Enhancing The Resilience Of Iot Networks: Strategies And Measures For Mitigating Ddos Attacks. *Cont.& Math. Sci.*, Vol.-19, No.-10, 129-152, October 2024 <https://jmcms.s3.amazonaws.com/wp-content/uploads/2024/10/10072102/jmcms-2410025-ENHANCING-THE-RESILIENCE-OF-IOT-NETWORKS-MF-HK.pdf>
- [44] Javed, M. A., Anjum, M., Ahmed, H. A., Ali, A., Shahzad, H. M., Khan, H., & Alshahrani, A. M. (2024). Leveraging Convolutional Neural Network (CNN)-based Auto Encoders for Enhanced Anomaly Detection in High-Dimensional Datasets. *Engineering, Technology & Applied Science Research*, 14(6), 17894–17899.
- [45] Li, H.; Luo, L.; Wang, H. Federated learning on non-independent and identically distributed data. In *Proceedings of the Third International Conference on Machine Learning and Computer Application (ICMLCA 2022)*, Shenyang, China, 16–18 December 2023; SPIE: Bellingham, WA, USA; pp. 154–162.
- [46] <https://ppl-ai-file-upload.s3.amazonaws.com/web/directfiles/attachments/66751900/153c4141-0a64-4d06-8a6d-74697c9ede74/Automated-Incident-Response-Systems-for-IoT-Security->

Breaches.docx

- [47] Gularte, K.H.M.; Vargas, J.A.R.; Da Costa, J.P.J.; Da Silva, A.A.S.; Santos, G.A.; Wang, Y.; Müller, C.A.; Lipps, C.; Júnior, R.T.S.; Vidal Filho, W.B.; et al. Safeguarding the V2X Pathways: Exploring the Cybersecurity Landscape through Systematic Literature Review. *IEEE Access* 2024, 12, 72871–72895.
- [48] Y. A. Khan, M. Ibrahim, M. Ali, H. Khan, E. Mustafa, "Cost Benefit Based Analytical Study of Automatic Meter Reading (AMR) and Blind Meter Reading (BMR) used by PESCO (WAPDA)", In 2020 3rd International Conference on Computing, Mathematics and Engineering Technologies (iCoMET), IEEE., pp. 1-7, Aug. 2020
- [49] Mustafa, M., Ali, M., Javed, M. A., Khan, H., Iqbal, M. W., & Ruk, S. A. (2024). Berries of Low-Cost Smart Irrigation Systems for Water Management an IoT Approach. *Bulletin of Business and Economics (BBE)*, 13(3), 508-514.
- [50] Hassan, A., Khan, H., Ali, A., Sajid, A., Husain, M., Ali, M., ... & Fakhar, H. (2024). An Enhanced Lung Cancer Identification and Classification Based on Advanced Deep Learning and Convolutional Neural Network. *Bulletin of Business and Economics (BBE)*, 13(2), 136-141.
- [51] Rahman, M. U., Khan, S., Khan, H., Ali, A., & Sarwar, F. (2024). Computational chemistry unveiled: a critical analysis of theoretical coordination chemistry and nanostructured materials. *Chemical Product and Process Modeling*, 19(4), 473-515.
- [52] Naz, H. Khan, I. Ud Din, A. Ali, and M. Husain, "An Efficient Optimization System for Early Breast Cancer Diagnosis based on Internet of Medical Things and Deep Learning", *Eng. Technol. Appl. Sci. Res.*, vol. 14, no. 4, pp. 15957–15962, Aug. 2024
- [53] Khan, I. Ullah, M. U. Rahman, H. Khan, A. B. Shah, R. H. Althomali, M. M. Rahman, "Inorganic-polymer composite electrolytes: basics, fabrications, challenges and future perspectives", *Reviews in Inorganic Chemistry.*, vol. 44, no. 3, pp. 1-2, Jan. 2024
- [54] Tatipatri, N.; Arun, S. A Comprehensive Review on Cyber-attacks in Power Systems: Impact Analysis, Detection and Cyber security. *IEEE Access* 2024, 12, 18147–18167.
- [55] Singh, A.; Abosaq, H.A.; Arif, S.; Mushtaq, Z.; Irfan, M.; Abbas, G.; Ali, A.; Al Mazroa, A. Securing Cloud-Encrypted Data: Detecting Ransomware-as-a-Service (RaaS) Attacks through Deep Learning Ensemble. *Comput. Mater. Contin.* 2024, 79, 857–873.
- [56] Zaheer, M., Azeem, M. H., Afzal, Z., & Karim, H. (2024). Critical Evaluation of Data Privacy and Security Threats in Federated Learning: Issues and Challenges Related to Privacy and Security in IoT. *Spectrum of Engineering Sciences*, 2(5), 458-479.
- [57] Ali, I., Saleem, M. U., Khan, A. A., Naz, A., Nawaz, M., & Khan, H. (2025). An

- Enhanced Artificial Intelligence Generated Virtual Influencer Framework: Examining the Effects of Emotional Display on User Engagement based on Convolutional Neural Networks (CNNs). *Annual Methodological Archive Research Review*, 3(4), 184-209.
- [58] Ayub, N., Sarwar, N., Ali, A., Khan, H., Din, I., Alqahtani, A. M., ... & Ali, A. (2025). Forecasting Multi-Level Deep Learning Autoencoder Architecture (MDLAA) for Parametric Prediction based on Convolutional Neural Networks. *Engineering, Technology & Applied Science Research*, 15(2), 21279-21283.
- [59] Mumtaz, J., Rehman, A. U., Khan, H., Din, I. U., & Tariq, I. Security and Performance Comparison of Window and Linux: A Systematic Literature Review. *Securing the Digital Realm*, 272-280.
- [60] Khan, H., Ali, A., & Alshmrany, S. (2023). Energy-Efficient Scheduling Based on Task Migration Policy Using DPM for Homogeneous MPSoCs. *Computers, Materials & Continua*, 75(1).
- [61] Ali, R., Khan, H., Arif, M. W., Tariq, M. I., Din, I. U., Afzal, A., & Khan, M. A. Authentication of User Data for Enhancing Privacy in Cloud Computing Using Security Algorithms. In *Securing the Digital Realm* (pp. 187-200). CRC Press.
- [62] Noor, H., Khan, H., Din, I. U., Tarq, M. I., Amin, M. N., & Fatima, M. (2025). 12 Virtual Memory Management. *Securing the Digital Realm: Advances in Hardware and Software Security, Communication, and Forensics*, 126.
- [63] Ayub, N., Iqbal, M. W., Saleem, M. U., Amin, M. N., Imran, O., & Khan, H. (2025). Efficient ML Technique for Brain Tumor Segmentation, and Detection, based on MRI Scans Using Convolutional Neural Networks (CNNs). *Spectrum of Engineering Sciences*, 3(3), 186-213.
- [64] Yousaf, M., Khalid, F., Saleem, M. U., Din, M. U., Shahid, A. K., & Khan, H. (2025). A Deep Learning-Based Enhanced Sentiment Classification and Consistency Analysis of Queries and Results in Search Using Oracle Hybrid Feature Extraction. *Spectrum of Engineering Sciences*, 3(3), 99-121.
- [65] Khan, H., Usman, R., Ahmed, B., Hashimi, U., Najam, Z., & Ahmad, S. (2019). Thermal-aware real-time task schedulability test for energy and power system optimization using homogeneous cache hierarchy of multi-core systems. *Journal of Mechanics of Continua and Mathematical Sciences*, 14(4), 442-452.
- [66] Mumtaz, J., Rehman, A. U., Khan, H., Din, I. U., & Tariq, I. Security and Performance Comparison of Window and Linux: A Systematic Literature Review. *Securing the Digital Realm*, 272-280.
- [67] Naveed, A., Khan, H., Imtiaz, Z., Hassan, W., & Fareed, U. (2024). Application and

- Ethical Aspects of Machine Learning Techniques in Networking: A Review. Spectrum of engineering sciences, 2(3), 455-501.
- [68] Sarwar, H. Khan, I. Uddin, R. Waleed, S. Tariq, "An Efficient E-Commerce Web Platform Based on Deep Integration of MEAN Stack Technologies", Bulletin of Business and Economics (BBE)., vol. 12, no. 4, pp. 447-453, Jun. 2023
- [69] Asghar, M. A., Aslam, A., Bakhet, S., Saleem, M. U., Ahmad, M., Gohar, A., & Khan, H. (2025). An Efficient Integration of Artificial Intelligence-based Mobile Robots in Critical Frames for the Internet of Medical Things (IoMTs) Using (ADP2S) and Convolutional Neural Networks (CNNs). Annual Methodological Archive Research Review, 3(4), 160-183.
- [70] Jabeen, T., Mehmood, Y., Khan, H., Nasim, M. F., & Naqvi, S. A. A. (2025). Identity Theft and Data Breaches How Stolen Data Circulates on the Dark Web: A Systematic Approach. Spectrum of engineering sciences, 3(1), 143-161.
- [71] Khan, A. K., Bakhet, S., Javed, A., Rizwan, S. M., & Khan, H. (2025). Framework for Predicting Customer Sentiment Aware Queries and Results in Search Using Oracle and Machine Learning. Spectrum of Engineering Sciences, 3(2), 588-617.
- [72] Abdullah, M. M., Khan, H., Farhan, M., & Khadim, F. (2024). An Advance Machine Learning (ML) Approaches for Anomaly Detection based on Network Traffic. Spectrum of engineering sciences, 2(3), 502-527.
- [73] Hashmi, U., & ZeeshanNajam, S. A. (2023). Thermal-Aware Real-Time Task Schedulability test for Energy and Power System Optimization using Homogeneous Cache Hierarchy of Multi-core Systems. Journal of Mechanics of Continua and Mathematical Sciences, 14(4), 442-452.
- [74] P. Mathur, Overview of machine learning in healthcare, in: Machine Learning Applications using Python, A Press, Berkeley, CA, 2019, pp. 1-11.
- [75] P. Guleria, M. Sood, Intelligent learning analytics in healthcare sector using machine learning, in: Machine Learning with Health Care Perspective, Springer, Cham, 2020, pp. 39-55.
- [76] Sultan, H., Rahman, S. U., Munir, F., Ali, A., Younas, S., & Khan, H. (2025). Institutional dynamics, innovation, and environmental outcomes: a panel NARDL analysis of BRICS nations. Environment, Development and Sustainability, 1-43.
- [77] Hussain, M., Ahmed, H. A., Babar, M. Z., Ali, A., Shahzad, H. M., Rehman, S. U., ... & Alshahrani, A. M. (2025). An Enhanced Convolutional Neural Network (CNN) based P-EDR Mechanism for Diagnosis of Diabetic Retinopathy (DR) using Machine Learning. Engineering, Technology and Applied Science Research, 15(1), 19062-19067.

- [78] Hussain, S., Sarwar, N., Ali, A., Khan, H., Din, I., Alqahtani, A. M., ... & Ali, A. (2025). An Enhanced Random Forest (ERF)-based Machine Learning Framework for Resampling, Prediction, and Classification of Mobile Applications using Textual Features. *Engineering, Technology & Applied Science Research*, 15(1), 19776-19781.
- [79] Khan, H., Imtiaz, M. A., Siddique, H., Rana, M. T. A., Ali, A., Baig, M. Z., ... & Alsaawy, Y. (2025). An Enhanced Task Migration Technique Based on Convolutional Neural Network in Machine Learning Framework.
- [80] Fawy, K. F., Rodriguez-Ortiz, G., Ali, A., Jadeja, Y., Khan, H., Pathak, P. K., ... & Rahman, J. U. (2025). Catalytic exploration metallic and nonmetallic nano-catalysts, properties, role in photoelectrochemistry for sustainable applications. *Reviews in Inorganic Chemistry*, (0).
- [81] Liaqat, M. S., Sharif, N., Ali, A., Khan, H., Ahmed, H. N., & Khan, H. (2024). An Optimal Analysis of Cloud-based Secure Web Applications: A Systematic Exploration based on Emerging Threats, Pitfalls and Countermeasures. *Spectrum of engineering sciences*, 2(5), 427-457.
- [82] Khawar, M. W., Salman, W., Shaheen, S., Shakil, A., Iftikhar, F., & Faisal, K. M. I. (2024). Investigating the most effective AI/ML-based strategies for predictive network maintenance to minimize downtime and enhance service reliability. *Spectrum of Engineering Sciences*, 2(4), 115-132.
- [83] Ahmad, J., Salman, W., Amin, M., Ali, Z., & Shokat, S. (2024). A Survey on Enhanced Approaches for Cyber Security Challenges Based on Deep Fake Technology in Computing Networks. *Spectrum of Engineering Sciences*, 2(4), 133-149.
- [84] Ayub, N., Ejaz, A., Hassan, B., Hussain, M. Z., Nadeem, M., Sabir, L., & Fatima, S. (2025). An Efficient Machine Learning And Deep Learning Based Deep Packet Security Framework For Detection Of Computing Network Faults In The Iots. *Spectrum of Engineering Sciences*, 3(5), 659-674.
- [85] Gordon, T. & Kannel, W. B. Multiple risk functions for predicting coronary heart disease: The concept, accuracy, and application. *Am. Heart J.* 103, 1031-1039 (1982).
- [86] Ayub, N., Imtiaz, M. A., Ali, E., Alqahtani, A. M., Ali, A., Ashurov, M., ... & Law, F. L. (2025). A Decision Framework for Intra Task Fixed Priority INTEL PXA270 Distributed Architecture for Soft RT-Applications Based on Deep Learning. *Engineering, Technology & Applied Science Research*, 15(3), 23553-23558.
- [87] Ayub, N., Waheed, A., Ahmad, S., Akbar, M. H. A., Fuzail, M. Z., & Hashmi, A. H. (2025). Strengthening Network Security: An Efficient DL Enabled Data Protection and Privacy Framework for Threat Mitigation and Vulnerabilities Detection in IoT

Network. Annual Methodological Archive Research Review, 3(6), 1-25.

- [88] Wilson, P. W. F. et al. Prediction of coronary heart disease using risk factor categories. *Circulation* 97, 1837–1847 (1998).
- [89] Splunk Inc. State of Security 2024. 2024. Available online: https://www.splunk.com/en_us/form/state-of-security.html (accessed on 1 October 2024).
- [90] Chapman, R. Ransomware Cases Increased by 73% in 2023 Showing Our Actions Have not Been Enough to Thwart the Threat. 2024. Available online: <https://www.sans.org/blog/ransomware-cases-increased-greatly-in-2023/> (accessed on 3 October 2024).
- [91] Ayub, N., Habib, Z., Bakhet, S., Riaz, S., Rizwan, S. M., Abid, M., ... & Khan, H. (2025). An Optimal Ai & Deep Learning Mechanism For Mitigating Hacking Threat Identification Using Secure Network Infrastructure Based On Linux And Software-Defined Network (Sdn). *Spectrum of Engineering Sciences*, 3(5), 675-687.
- [92] Zebrack, J. S. et al. Usefulness of high-sensitivity C-Reactive protein in predicting long-term risk of death or acute myocardial infarction in patients with unstable or stable angina pectoris or acute myocardial infarction. *Am. J. Cardiol.* 89, 145–149 (2002).
- [93] Whittaker, Z. The Biggest Data Breaches in 2024: 1 Billion Stolen Records and Rising. Available online: <https://techcrunch.com/2024/08/12/2024-in-data-breaches-1-billion-stolen-records-and-rising/> (accessed on 6 October 2024).
- [94] Greenberg, A. Medical-Targeted Ransomware Is Breaking Records After Change Healthcare's \$22M Payout. 2024. Available online: <https://www.wired.com/story/change-healthcare-22-million-payment-ransomware-spike/> (accessed on 6 October 2024).
- [95] Smith, G. Ransomware Statistics for 2024: Latest Trends & Attack Methods. 2024. Available online: <https://www.stationx.net/ransomware-statistics/> (accessed on 28 September 2024).
- [96] Mazhar, M.S.; Saleem, Y.; Almogren, A.; Arshad, J.; Jaffery, M.H.; Rehman, A.U.; Shafiq, M.; Hamam, H. Forensic Analysis on Internet of Things (IoT) Device Using Machine-to-Machine (M2M) Framework. *Electronics* 2022, 11, 1126.
- [97] Qureshi, S.; Tunio, S.; Akhtar, F.; Wajahat, A.; Nazir, A.; Ullah, F. Network Forensics: A Comprehensive Review of Tools and Techniques. *Int. J. Adv. Comput. Sci. Appl.* 2021, 12.
- [98] Ayub, N., Anwer, M. A., Iqbal, A., Rizwan, S. M., Shahbaz, A., Abid, M. H., & Rafi, S. (2025). Enhanced ML Framework based on Artificial Neural Network for

- countermeasures of Data Protection and Network Vulnerabilities Detection in Industrial Internet of Things. *Annual Methodological Archive Research Review*, 3(5), 410-431.
- [99] Ghabban, F.M.; Alfadli, I.M.; Ameerbakhsh, O.; AbuAli, A.N.; Al-Dhaqm, A.; Al-Khasawneh, M.A. Comparative analysis of network forensic tools and network forensics processes. In *Proceedings of the 2021 2nd International Conference on Smart Computing and Electronic Enterprise (ICSCEE)*, Cameron Highlands, Malaysia, 15–17 June 2021; pp. 78–83. [Google Scholar]
- [100] Breitingner, F.; Hilgert, J.N.; Hargreaves, C.; Sheppard, J.; Overdorf, R.; Scanlon, M. DFRWS EU 10-year review and future directions in Digital Forensic Research. *Forensic Sci. Int. Digit. Investig.* 2024, 48, 301685. [Google Scholar] [CrossRef]
- [101] Nandita, G.; Munesh Chandra, T. Malicious host detection and classification in cloud forensics with DNN and SFLO approaches. *Int. J. Syst. Assur. Eng. Manag.* 2024, 15, 578–590.
- [102] Pandey, B.; Pandey, P.; Kulmuratova, A.; Rzaeva, L. Efficient usage of web forensics, disk forensics, and email forensics in the successful investigation of cybercrime. *Int. J. Inf. Technol.* 2024, 16, 3815–3824.
- [103] Alam, M.N.; Kabir, M.S. Forensics in the Internet of Things: Application Specific Investigation Model, Challenges and Future Directions. In *Proceedings of the 2023 4th International Conference for Emerging Technology (INCET)*, Belgaum, India, 26–28 May 2023; pp. 1–6. [Google Scholar]
- [104] Zhang, H. Simulation of network forensics model based on wireless sensor networks and inference technology. *Meas. Sens.* 2024, 34, 101261.
- [105] Kamble, D.; Rathod, S.; Bhelande, M.; Shah, A.; Sapkal, P. Correlating forensic data for enhanced network crime investigations: Techniques for packet sniffing, network forensics, and attack detection. *J. Auton. Intell.* 2024, 7, 1272.
- [106] Ferrag, M.A.; Ndhlovu, M.; Tihanyi, N.; Cordeiro, L.C.; Debbah, M.; Lestable, T.; Thandi, N.S. Revolutionizing cyber threat detection with large language models: A privacy-preserving bert-based lightweight model for iot/iiot devices. *IEEE Access* 2024, 12, 23733–23750.
- [107] Moustafa, N.; Koroniotis, N.; Keshk, M.; Zomaya, A.Y.; Tari, Z. Explainable Intrusion Detection for Cyber Defences in the Internet of Things: Opportunities and Solutions. *IEEE Commun. Surv. Tutor.* 2023, 25, 1775–1807.
- [108] Alspach, K. Network Security Devices Are the Front Door to an IT Environment, But Are They Under Lock and Key? *CRN Article*. 2024. Available

online: <https://www.crn.com/news/security/2024/network-security-devices-are-the-front-door-to-an-it-environment-but-are-they-under-lock-and-key> .

- [109] Chen, Y.; Cui, M.; Wang, D.; Cao, Y.; Yang, P.; Jiang, B.; Lu, Z.; Liu, B. A survey of large language models for cyber threat detection. *Comput. Secur.* 2024, 145, 104016.
- [110] Gupta, M.; Akiri, C.; Aryal, K.; Parker, E.; Praharaj, L. From chatgpt to threatgpt: Impact of generative ai in cybersecurity and privacy. *IEEE Access* 2023, 11, 80218–80245.
- [111] Jabeen, T., Mehmood, Y., Khan, H., Nasim, M.F. and Naqvi, S.A.A., 2025. Identity Theft and Data Breaches How Stolen Data Circulates on the Dark Web: A Systematic Approach. *Spectrum of engineering sciences*, 3(1), pp.143-161.
- [112] Zeadally, S.; Adi, E.; Baig, Z.; Khan, I.A. Harnessing artificial intelligence capabilities to improve cybersecurity. *IEEE Access* 2020, 8, 23817–23837.
- [113] Wiafe, I.; Koranteng, F.N.; Obeng, E.N.; Assyne, N.; Wiafe, A.; Gulliver, S.R. Artificial intelligence for cybersecurity: A systematic mapping of literature. *IEEE Access* 2020, 8, 146598–146612.